



## **tesa 4089 PV0 Impreso** **Cinta de embalaje de uso general**

### **Descripción de Producto/Aplicación:**

tesa 4089 PV0 se basa en un soporte de PP con adhesivo de caucho natural base solvente.

tesa 4089 PV0 esta disponible en tres colores.

tesa 4089 PV0 se usa universalmente para cerrar cajas de cartón de peso medio bajo.

tesa 4089 Se puede usar con todos los dispensadores manuales y automáticos comunes.

### **Dimensiones:**

|             |                 |
|-------------|-----------------|
| Longitudes: | 66, 132, 1000 m |
| Anchos:     | 38, 50, 75 mm   |

Otras dimensiones bajo demanda

### **Datos Técnicos:** **(Valores Medios)**

| Soporte | Colores                         | Espesor<br>Soporte / total <sup>1)</sup> | Adhesión    | Resistencia a la<br>tensión <sup>1)</sup> | Elongación a la<br>rotura <sup>1)</sup> |
|---------|---------------------------------|------------------------------------------|-------------|-------------------------------------------|-----------------------------------------|
| PP      | transparente,<br>habana, blanco | 32 ym / 51 µm                            | 1,9 N/10 mm | 50 N/10 mm                                | 140 %                                   |

<sup>1)</sup> Parámetros de especificación

3540 – 03/10



tesa self adhesive tapes are used in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We, therefore, recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The advisory section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty. The contents of this product information correspond with the current technical level and may change due to further development.